

## Crystal Bakery Upright

### Features:

- Designed for 43°C ambient environment
- State of the art control panel with easy to read LED display for temperature control and diagnostics
- Top mounted removable refrigeration system for easy service and maintenance
- Forced air refrigeration system
- Auto defrost
- Waste heat recovery vaporizer
- Automatic door fan cut off switch on all freezer models
- Self closing doors with easy to clean handles
- Heavy duty swivel and brake castors
- Supplied with 20 x 18" x 30" tray slides or 16" x 30" tray slides to suit bakers trays (trays and shelves excluded)
- Can accommodate 600mm x 400mm trays
- 75mm spacing between slides
- Can be fitted with shelf stripping
- Hermetique compressor

## Crystal



Model	C1	C2
Capacity	20 tray: 730 litres	40 tray: 1630 litres
<b>Finish: Stainless steel interior and exterior*</b>		
Refrigerator Solid Door +1°/+4°C kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>HC1TSS</b> 160/4.0/520	<b>HC2TSS</b> 230/5.3/750
Freezer Solid door -18°/-22°C kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>LC1TSS</b> 160/4.5/700	<b>LC2TSS</b> 230/5.4/1020
<b>Finish: White Colorbond® interior and exterior with stainless steel internal floor*</b>		
Refrigerator Solid Door +1°/+4° kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>HC1TCB</b> 160/4.0/520	<b>HC2TCB</b> 230/5.3/750
Freezer Solid door -18°/-22°C kg-unpacked / Amps-run / Wr-refrigeration Watts (nom.)	<b>LC1TCB</b> 160/4.5/700	<b>LC2TCB</b> 230/5.4/1020

\*Refer notes page 8

Gas: Self-contained fridge R134a@-5C SST  
Self-contained freezer R404a@-30C SST  
Remote units R404a (others available)

Electrical lead length 1.5m min. 240V 50Hz

Heat rejection self-contained units: Fridge 1.4xWr, Freezer 1.6xWr

Options (see page 8):

Cylindrical locks

