

## www.aonemaster.com.au

07 3841 2920

2/41 Darnick Street, Underwood QLD 4119 sales@aonemaster.com.au

## TOP MOUNT GLASS DOOR

REFRIGERATOR
MODEL: KR25-1G

## 

#### **■ DIGITAL TEMPERATURE CONTROL SYSTEM**

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

### ■ HIGH-TECH MONITOR

The monitor digitally displays present cabinet temperatures. You can easily change the temperature by adjusting the thermostat.

#### ■ HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

#### **■ EFFICIENT REFRIGERATION SYSTEM**

Turbo Air's solid door reach-in's are designed with oversized and balanced refrigeration systems. CFC Free R-134A utilized for refrigerator and R-404A for freezer. These include efficient evaporators and condensers for faster cooling and greater efficiency.

## ■ AUTOMATIC EVAPORATOR FAN MOTOR DELAYS

Through stopping the evaporator fan when the refrigerator door opens, the circulation of hot, moist air into the refrigerator is prevented. This increases energy efficiency and lengthens the life of the compressor.

# ■ ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) COATED WIRE SHELVES

## ■ EXTERIOR & INTERIOR OF CABINET CONSTRUCTION

Stainless steel exterior (galvanized steel top, bottom and back) and stainless steel interior with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury.

### ■ High-Density Polyurethane Insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

## ■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.



Model	Swing Door	Capacity (litres)	#of Shelves	НР	AMPS	Crated Weight (kg)	W x D x H
KR25-1G	1	574	3	1/4	2.8	87	640 x 800 x 1926

# **TOP MOUNT GLASS DOOR**

REFRIGERATOR
MODEL: KR25-1G

(unit: mm)

Model: KR25-1G

SPEC SHEET	KR25-1G		
Classification	Refrigerator		
Cabinet dimension (WxDxH mm)	640x800x1926		
Capacity (Liters)	574		
Inner Temperature	1°c ~ 8°c		
Ambient Temperature	40°c		
Doors	1		
# of shelves	3		
Refrigerant	R-134a		
Compressor (HP)	1/4		
Cooling Type	Fan cooling type		
Inculation Type	Polyurethane/		
Insulation Type	Cyclopentane+CFC Free		
Temperature Control Type	Digital		
Amps (A)	2.8		
Voltage (V/Hz/Ph)	240V 50Hz 1Ph		
Power (W)	314		
Weight (Kg)	87		


Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.


- Door Locks Standard
- INTERIOR LED LIGHTING STANDARD
- SELF-CONTAINED SYSTEM
- STANDARD 3" SWIVEL CASTERS WITH LOCKS ON THE FRONT SET
- SOLID AND STURDY GRILLE DESIGN
- ALUMINIUM DOOR FRAME
- Low-E Double Glass





## PLAN VIEW





SIDE VIEW

www.aonemaster.com.au

07 3841 2920, 0452 388 174
2/41 Darnick Street, Underwood QLD 4119
sales@aonemaster.com.au